

PARSUN OUTBOARD ENGINE

PARSUN

F25BMS
 MODEL : *F25BML*
F25FWL

4Stroke 25 HP



Specification

MODEL	Unit	F25BMS	F25BML	F25FWL
Overall length	mm(in.)	1151(45.3)		703(27.7)
Overall width	mm(in.)	430(16.9)		376(14.8)
Overall height	mm(in.)	1153(45.4)	1280(50.4)	
Transom height	mm(in.)	381(15)	508(20.0)	
Weight	kg	66	68	70
Full throttle operating range	r/min	5000-6000		
Maximum output	kw(HP)@r/min	18.4(25)@5500		
Idling speed(Neutral)	r/min	925-1025		
Engine type		4-Stroke OHV		
Cylinders		L2		
Displacement	cm ³	498		
Bor x stroke	mm(in.)	65.0x75.0(2.56x2.95)		
Ignition system		CDI		
Control system		Tiller control		Remote control
Starting system		Manual start		Electric start
Gear positions		Forward-Neutral-Reverse		
Gear ratio		2.08(27/13)		
Trim and tilt system		Manual tilt		
Fuel tank capacity	L	24		
Maximum fuel waste	L/h	9.2		
Engine oil capacity	L	1.7		
Gear oil capacity	cm ³	320		
Propeller options	in	3-9 ⁷ / ₈ "x11 ¹ / ₄ "		

ติดต่อ www.twineye.com

อาคารเทพนคร ถนนบางนา-ตราด กม.1
 Tel.0-2399-3692 , 0-2399-3693